

Design Your Business Communications with iPECS UCP

iPECS
Your Communications Solution

iPECS UCP is Ericsson-LG Enterprise's Unified Communications Platform designed to meet SME and Enterprise communications needs. As ground breaking innovative platform, iPECS UCP provides out of box UC and Mobility solution. In addition, iPECS UCP is scalable for premium UC solution.

Embedded UC and Telephony

As the most compelling advantage, UC features are embedded in iPECS UCP. Users can improve business efficiency and productivity with embedded UC features including real-time voice, video and presence enabled IM with messaging services (Visual Voice Mail and SMS etc.) under a single user interface on multiple devices.

Rich Business Applications

iPECS UCP provides a various range of applications and mobile clients to fulfill varying needs and requirements in the SME environments. Also, it offers interoperability with various 3rd party solutions in hospitality, healthcare and other vertical industries.

Wide Range of Mobility

iPECS UCP provides multiple mobility solutions to improve business productivity and decrease communication expenses. iPECS DECT and Wi-Fi phones provide feature rich and reliable communications for internal mobile workers. iPECS UCS mobile client delivers the power of a desk phones to smartphones or tablet PCs for external mobile workers.

Ultimate Flexibility on Deployment

iPECS UCP as "Modular ALL-IP Architecture" enables flexible and cost-effective multi-site deployment with industry-unique architecture. Furthermore, virtualized deployment is supported to maximize flexibility on deployment as well. (iPECS vUCP is needed) It can be fully networked in T-NET (Transparent Networking) or Networking mode for local survivability and PSTN failover. Also, it provides call server (Local/Geo) and power redundancy for seamless communications environment. Through flexible T-NET and redundancy features, IT managers can easily manage a multi-site architecture. Leverage your business to full of flexibility with wide range of deployment scenarios.

Seamless Scalability

As a scalable call server iPECS UCP allows businesses to easily expand capacity with optional gateways or boards. In addition, simple system port licensing enables upfront investment savings and cost-effective expansion as a business grows. Not only system capacity, communications features including UC solution also can be expanded or added with simple license.

Virtualize Your Business Communications

iPECS vUCP (virtual UCP) is the first iPECS Unified product for virtualization solution. iPECS vUCP, as a software base call server is running on VMware virtual environment. The software is same as on-premise iPECS UCP and all the system features as well. Under the equal user experiences, iPECS vUCP will make easy to deploy your business communication's flexibility and scalability. Also, it delivers an innovative way to manage diverse business applications and collaborate cost-effectively, so you can leverage business communications while keeping all the advantages of iPECS UCP.



Key Features

- Built-in iPECS UCS
- Built-in iPECS ClickCall
- Embedded VoIP
- Embedded Voice Mail
- Embedded ACD
- Embedded SIP
- Embedded audio conference
- Embedded hotel features
- Mobile extension
- One number service
- Web call back
- ACD call statistics for multiple group
- Emergency/Alarm call service
- Simplified directory search and dial
- Custom MOH support
- VM to E-Mail forwarding
- Centralized Voice Mail
- Centralized control T-NET
- System geographic redundancy
- Web administration
- Web user portal
- Virtualization with iPECS vUCP

Applications

- iPECS UCS
- iPECS ClickCall
- iPECS RCC Gateway
- iPECS Attendant (Office/Hotel)
- iPECS IPCR
- iPECS CCS
- iPECS Report Plus
- iPECS NMS

Supported Terminals

- LIP-9071
- LIP-9000 Series
- LDP-9200 Series
- GDC-800H (IP DECT)
- GDC-500H/480H
- WIT-400HE

3rd Party Applications and Middleware

- Microsoft Lync/SfB
- Fidelio I/F
- Tiger TMS for hospitality solution
- 3rd party PMS Interface
- LAS for healthcare solution
- TAPI (3rd Party)

On-Premise



UCP100
50~199 Port
By License



UCP600
100~600 Port
By License



UCP2400
600~2,400 Port
By License

Virtualization

vUCP
200~2,400 Port
By License



VMware
VMware enabled Data Center

System Capacity

Category	UCP100	UCP600	UCP2400	vUCP	Remark	
Main cabinet		10 Slot		-	10 th slot is for PSU	
System ports (Default)	199 (50)	600 (100)	2,400 (600)	2,400 (200)		
IP Extension (Default)	199 (30)	600 (10)	2,400 (10)	2,400 (10)		
CO/IP Line	199	600	998	-		
UCS Standard clients	Default Option 1 (Desktop/Mobile) Default Option 2 (Advanced User) Max	2/2 2 100	10/10 10 200	20/20 20 400	- 10 400	Only one default option can be used
UCS Premium clients	199	600	2,400	2,400		
Clickcall (Default)	199 (2)	600 (10)	2,400 (10)	2,400 (10)		
Server Redundancy	Local Geographical	- -	O O	O O	- w/ License	
Integrated Telephony ports	Standard Option	2FXS(SLT) 4CO or 2BRI or 4BRI	- -	- -	- -	
VoIP Channel	Built-in Basic* Built-in Max** System Max	2~6 16 199	6 24 600	- - 998	- 250 (per vVOIM) 998 (w/ vVOIM)	w/ License(8 ch increment) w/ VOIM and VCIM
Built-in Audio Conference	6/10/14/18	6/18	-	-	VoIP DSP channels can be assigned to the MCIU, 2 VoIP = 4 Conf channels	
VM Channel	Built-in Basic Built-in Max External Basic (UVM) External Max (UVM)	8 ch/4 hrs 8 ch/14 hrs	8 ch/6 hrs 8 ch/16 hrs 8 ch/50 hrs 16 ch/200 hrs	- - - 150 ch/500 hrs (vUVM)	- - - w/ License	
UVM/vUVM per system			30/0		30/1	
MCIM*** per system			30		30	
Attendant			50		50	
Serial Port (RS-232C) / USB (3.0) Host Port			1/1		-	

* In-band/Out-band SIP, Transcoding, Networking, Remote IP Phone/Devices

** Out-band SIP, Networking, Remote IP Phone/Devices

*** MCIM supports 4-32 party conferencing

Power Requirement

Item	Description	Specification
Module AC/DC Adapter	AC Voltage Input	100~240VAC +/- 10% @ 50/60Hz
	AC Current Input	1.0 amps
	DC Output	48 VDC @ 0.8 amps
	DC Output	48 VDC @ 0.8 amps
Keypad AC/DC Adapter	AC Voltage Input	100~240VAC +/- 10% @ 50/60Hz
	AC Current Input	0.2 amps
	DC Output	48 VDC @ 0.3 amps
	DC Output	48 VDC @ 0.3 amps
PSU	AC Voltage Input	100~240VAC +/- 10% @ 50/60Hz
	Fuse	T6.3, AC250V
	DC Output	48 VDC, 5.3 amps/5VDC @ 1 amps

Dimension & Weight

WxHxD (mm)	Standard Gateway Module	38.8 x 230 x 194.5
WxHxD (mm)	Main Cabinet, Enhanced	440 x 265.6 x 318.2
	19" Rack Mount modules	436.6 x 53 x 318
Weight (Kg)	Standard Gateway Module	1.5
	Main Cabinet, Enhanced (with PSU module)	7.78(9.32)
	19" Rack Mount modules	4.32

Operating Environment

Temperature	0(°C) - 40(°C)/32(°F) - 104(°F)
Humidity	0 - 80%(Non-condensing)

System Components

Item	Board	Description
UCP Call Server	UCP100	Unified Communications Platform Server 100, Basic 50, Up to 199 port
	UCP600	Unified Communications Platform Server 600, Basic 100, Up to 600 port
	UCP2400	Unified Communications Platform Server 2400, Basic 600, Up to 2,400 port
	vUCP	Virtual Unified Communications Platform, Basic 200, Up to 2,400 port
Trunk Gateway	VCIM*	VOIP/Audio conference Module
	VOIM8/24	8/24 ch VoIP Interface Module
	LGCM4/8	4/8 port Analog CO Interface Module
	BRIM2/4	2/4 BRI(4/8 ch) Interface Module
	PRIM	1 port PRI(30 ch) Interface Module
	vVOIM	Virtual VoIP Interface Module
Extension Gateway	DTIM8/24	8/24 port Digital Line Telephone Interface Module
	SLTM4/8/32	4/8/32 port Single Line Telephone Interface Module
	WTIM4/8/24	4/8/24 port Wireless Telephone Interface Module (DECT base controller)

* 64 DSP channels by default and expandable up to 128 DSP channels

VoIP and Audio Conference can be mixed use. 1 VoIP channel uses 2 DSP channels and 1 Audio Conference channel uses 1 DSP channel

The content of this document is subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson-LG Enterprise shall have no liability for any error or damage of any kind resulting from the use of this document

© Ericsson-LG Enterprise Co., Ltd. 2017 Version 1.1

Ericsson-LG Enterprise Co., Ltd.
(431-749) 77, Heungan-daero 81 beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, South Korea
www.ericssonlg-enterprise.com | www.iPECS.com | www.iPECS-Cloud.com

iPECS is an Ericsson-LG Brand

