



## VIDEO CONFERENCE AT YOUR DESK

Wizyconf offers you **the best videoconferencing experience ever**. Wildix Wizyconf videoconference solution is **fully integrated into the company communication system** and **does not require installation** of any additional software or hardware components.

Everything you need is the web browser. Easily start a videoconference with internal and external users right from your Collaboration web interface.

Wildix offers additional equipment to ensure the best user experience in small conference rooms — **Wizyconf-Huddle**.

## WIZYCONF HIGHLIGHTS



- Based on WebRTC
- No installation, plugin free
- Instant access via a link, also for external users
- Chat and private messaging, HD video & audio
- Access in audio-only mode possible
- Speaker auto-detection
- Tiles and Sidebar views
- Conference scheduling
- Desktop sharing
- Mute all/ Mute everyone except
- Conference recording (audio, video, screen sharing)
- Live streaming to Facebook, YouTube
- Raise a hand


## WIZYCONF-HUDDLE

A **huddle room** is a collaboration space of the future -- a small room, equipped with teleconferencing system, where 3-5 people can gather for short meetings to discuss projects, strategize and take decisions.

**Wizyconf-Huddle** is a Plug&Play solution for your Huddle Rooms.

### WIZYCONF-HUDDLE HIGHLIGHTS

- 120° wide angle webcam, Full HD
- No need of remote control
- 360° microphone
- All-in-one USB-C cable (USB-A adapter included)
- Portable case for easy transportation



### WIZYCONF-HUDDLE TECH SPECIFICATONS

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• Mechanically adjustable (up and down) lens: 1/2.8, fixed focus, 120° angle</li> <li>• Image sense: Full HD CMOS sensor</li> <li>• Video: 1080P (1920*1080 pixel)</li> <li>• OS: Windows / MacOS</li> <li>• Touch keypad: Mic on / off; Volume + / -</li> <li>• Omnidirectional microphone with 256ms acoustic echo cancellation and dynamic noise reduction</li> <li>• Network interface: USB-C(USB-A adapter included)</li> <li>• Power: USB cable supply (5V /500mA)</li> </ul> | <ul style="list-style-type: none"> <li>• Temperature: 5° - 55° C / 41° - 131° F</li> <li>• Storage: -10° - 55° C / 14° - 131° F</li> <li>• Humidity: 20-85% non-condensed</li> <li>• Noise level: &lt;48db</li> <li>• Full duplex audio</li> <li>• Loudspeaker: 10 adjustable ranges up to 94dBA; frequency response: 300 to 3400Hz</li> <li>• Weight: 465g</li> <li>• Size: 235*62*62mm</li> </ul> |
|--|---|