

SuperVision 5 is Prime VoIP office phone with WiFi, Bluetooth, 7-inch rotating touchscreen and wireless Bluetooth handset that's stylish and designed with C-suite in mind.

HIGHLIGHTS

- 7" color touchscreen 1024*600, adjustable (0° to 40 °)
- Bluetooth wireless handset
- Dual Ports 10/100/1000
- Max 59 BLF keys
- Built-in 2.4GHz/5GHz dual-band Wi-Fi 6 and Bluetooth 5.4
- Call history sync
- Presence monitoring
- Wideband HD audio
- Headset USB and BT Audio Support
- Caller image
- Antibacterial surface protection
- Incoming video streams



TECH SPECIFICATIONS

Phone & PBX

- Presence
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

Audio

- HD audio with wideband codec G.722, Opus
- Narrowband codec G.711a, G.729
- HD voice speaker
- Full-duplex Acoustic Echo Cancellor

Security and Standards

- SIP TLS; QoS VLAN; RTP/RTCP
- SRTP
- PoE IEEE 802.3af
- Wi-Fi Security Mode: WPA/WPA2-PSK/802.1X EAP

Network and Connectivity

- Built-in dual band Wi-Fi 6:
 - 2.4GHz, 802.11 b/g/n/ax
 - 5GHz, 802.11 a/n/ac/ax
- Built-in Bluetooth BLE 5.4

Supported Headsets

- RJ-9 connector, USB connector, Bluetooth
- MonoLED, DuoLED
- 3rd party headsets: <https://wildix.atlassian.net/wiki/x/DhTOAQ>

Physical

- 59 BLF keys (5 pages)
- 7" adjustable (0° to 40 °) color touchscreen 1024*600
- BT wireless handset:
 - Battery capacity: 300mAh
 - Size & weight: 203*46*42,3 mm, 18 g
 - Range: 10 m/ 32 feet
 - Talk time: 13 hours
 - Standby time: 14 hours
- Interfaces: 2 x RJ45 10/100/1000 Mb Ethernet ports, 1 x RJ9 headset port; 1 x RJ9 handset port; 1 x USB 2.0 port
- Optional Power Adapter (code: PS-12V2A): Input AC 100-240 V; Output DC 12 V / 1.5 A
- Max power consumption: 12,1W (PoE), 8,9W (Adapter)
- Giftbox size & weight: 270*258*71 mm, 1,65 kg
- Operating t°: 32~113 °F, 0~45°C; Storage t°: -22-140 °F, -30~60°C; Humidity: 10~95%
- Desktop stand/wall mounted

VoIP Phones datasheets:

