

WelcomeConsole 5 is perfect for monitoring high number of colleagues and handling medium to high volumes of calls.

HIGHLIGHTS

- 4.3" main color display, 480*272; 2x3.5" side color displays
- Dual Gigabit Ports 10/100/1000
- Max 106 BLF keys, including side displays, visual / audio BLF
- Call history sync
- Presence monitoring
- Caller image
- Wideband HD audio
- Headset USB Audio Support
- PoE IEEE 802.3af
- 802.3az Green Ethernet
- Built-in Bluetooth 4.2
- WiFi dongle-ready



TECH SPECIFICATIONS

Phone & PBX

- Presence
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

Audio

- HD audio with wideband codec G.722, Opus
- Narrowband codec G.711a, G.729
- HD voice speaker
- Full-duplex Echo canceller

Security & Networking

- SIP TLS; QoS VLAN; RTP/RTCP
- SRTP

Supported Headsets

- RJ-9 connector, USB connector, Bluetooth
- MonoLED, DuoLED
- 3rd party headsets: <https://wildix.atlassian.net/wiki/x/DhTOAQ>

Physical

- 106 BLF keys: 10 on the main display, 16 BLFs x 2 levels x 3 pages on the side screens
- 4.3" main color display, 480*272; 2x3.5" side color displays
- 1 x RJ9 headset port; 1 x RJ9 handset port; 1 x USB port
- WelcomeConsole optional Power Adapter (code: PS-5V2A): Input AC 100-240 V; Output DC 5 V / 2 A
- Max power consumption: 9W
- 2 x RJ45 10/100/1000 Mb Ethernet ports
- 802.3az Green Ethernet
- PoE IEEE 802.3af
- Giftbox size: 323*301*71 mm
- Operating t°: 32~113 °F, 0~45°C; Storage t°: -22~140 °F, -30~60°C; Humidity: 10~95%

VOIP Phones datasheets:

