

# **UNIVERGE® SV8500 Communications Server**



# The premier IP communications server for regional and global expansion, worker mobility and environmental responsibility.



#### At a Glance

- · Increase customer satisfaction and lower expenses
- Provides reliable business continuity support
- Supports open standards for simplified business process integration
- Delivers advanced applications
- · Complies with green standards
- · Seamless network integration
- Investment protection

#### **Overview**

The UNIVERGE SV8500 Communications Server is a powerful enterprise communications solution capable of supporting up to 4,000 endpoints in a single system. Reliable, scalable and energy-efficient, it is an advanced application server that supports voice, unified communications and mobility solutions for tens of thousands of users. Designed to easily and efficiently scale, the SV8500 meets the needs of the largest enterprises, supporting up to 192,000 ports in a networked environment.

As a part of NEC's UNIVERGE®360 commitment to putting people in the center of communications, the SV8500 unifies the enterprise through the high-efficiency technology that large enterprises require. The SV8500 is the premier IP communications server for regional and global expansion, worker mobility and environmental responsibility. It offers an extensive IP feature set in a flexible, scalable, secure package.

#### Solution

# Increase Customer Satisfaction and Lower Expenses

The SV8500 enables a business's customers to reach workers wherever they are. It extends communications to branch and international offices simply and cost-effectively. It supports a number of NEC's mobility-enhancing tools that empower users to be productive - whether they are at their desks or have stepped away. Individuals, departments and locations can work more efficiently by communicating seamlessly in real time.

### **Provides Business Continuity**

The SV8500 ensures business continuity through component redundancy. It also provides IP fail-over for stations and trunking, clustered survivability, power failure transfer and call routing for self-healing networks. Its architecture is ideal for mission-critical situations. Advanced fault diagnosis, error-correcting memory, and component redundancy all ensure high availability and operational continuity.



### Simplify Business Process Integration

The SV8500 provides support for open-standards for integrating communications into business process applications. This facilitates process simplification. Standards and devices supported by the SV8500 include:

- SIP-enabled devices
- LDAP-compliant databases
- Java<sup>™</sup> and XML
- Managed data network infrastructure
- UC for Enterprise Applications Platform (UNIVERGE OW5000), an integration platform for UC solutions such as NEC's UC for Enterprise suite of applications, Microsoft® Office Communications Server and IBM® Lotus® Sametime®

# Delivers Advanced Applications

The SV8500 provides cutting-edge features that optimize the customer experience and maximize enterprise resources. Some of the applications supported are:

- NEC's UC for Enterprise (UCE) suite of applications which include UCE Unified Messaging, UCE Desktop Client, UCE Attendant, UCE Collaboration, UCE Mobility and Contact Center. This suite of applications provides unified communications, fixed mobile convergence, contact center and attendant capabilities, and advanced collaboration tools.
- UC for Enterprise Manager, a web-based management application that enables users to access the system remotely through a personalized portal to configure their communications options. Additionally, Expense Management offers call accounting, asset management, mobile management, and billing and invoice reconciliation.

- UNIVERGE DT700/DT300 Series Desktop Terminals raise the standard with an extensive feature set, XML application support and a revolutionary modular design.
- NEC's softphones which integrate communications into the computing environment to eliminate the need for a physical phone and extend the desktop around the world.

# Supports Green Initiatives

The SV8500 is an ecologically sound, compact system that uses 23% less power than previous generations of IP communication servers. NEC paid special attention to its environmental impact and delivered a RoHS compliant system that includes:

- · Reduced air conditioning requirements for the server
- Recyclable materials and components that use environmentally safe chemicals
- Elimination of lead and mercury in circuit boards
- Documentation provided in electronic format rather than paper hooklets

# Seamless Network Integration

The SV8500 can be incorporated into networks that contain existing NEC systems to provide a path to IP. The SV8500's interoperability enables it to protect a business's investment in previous products such as the UNIVERGE SV7000 Communications Server, the NEAX® 2400 ICS, IMX and the UNIVERGE NEAX 2400 IPX.

Using both FCCS (Fusion) and CCIS networking for seamless integration, the SV8500 can also be networked with other NEC products, including the NEAX 2000 IPS, and the UNIVERGE SV8100 and SV8300 Communications Servers. This provides businesses with a broad range of server options to address needs at the edge of the network as well as the core.

## **SV8500 Communications Server**

#### **Investment Protection**

For existing customers, NEC has developed an easy way to transition existing NEAX® 2400 ICS, IMX, UNIVERGE NEAX 2400 IPX or UNIVERGE SV7000 Communications Servers into a full-featured IP communications system that supports advanced business productivity applications. This protects our customer's initial investment and extends the life of their current voice infrastructure.

#### **Specifications**

T1/PRI Channels:* 4,000  SIP Trunks:* 4,000  Stations  Digital Terminals:* 4,000  Analog Terminals:* 4,000  IP Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations		
Processors Intel Dual Core Duo 2.16GHz  Gateway Chassis Slots 17  Number of Ports 6,144  Trunks  Analog Trunks (COT):* 4,000 T1/PRI Channels:* 4,000 SIP Trunks:* 4,000 Stations Digital Terminals:* 4,000 IP Terminals (hard/soft): 4,000 IP Terminals (hard/soft): 4,000  Networking FCCS networking (IP): 64 nodes CCIS networking (T1/IP): 64 nodes Ports: up to 192,000  Standards Devices: SIP-enabled Databases: LDAP-compliant Languages: Java and XML Wireless LAN: 802.11 a/b/g Other: 802.3af  Applications Internal ACD: Max 1000 stations OAI support: UNIVERGE 3rd party apps Conference Bridge: Max 32 ports/card; Max 255 cards	Dimensions	3 Rack Units high, 19 inches wide
Gateway Chassis Slots         17           Number of Ports         6,144           Trunks         4,000           T1/PRI Channels:*         4,000           SIP Trunks:*         4,000           Stations         4,000           Digital Terminals:*         4,000           Analog Terminals:*         4,000           IP Terminals (hard/soft):         4,000           Networking         FCCS networking (IP):         64 nodes           CCIS networking (IT1/IP):         64 nodes           Ports:         up to 192,000           Standards         Devices:         SIP-enabled           Databases:         LDAP-compliant           Languages:         Java and XML           Wireless LAN:         802.11 a/b/g           Other:         802.3af           Applications           Internal ACD:         Max 1000 stations           OAI support:         UNIVERGE 3rd party apps           Conference Bridge:         Max 32 ports/card; Max 255 cards	System Voltage	100-240V AC or -48 VDC
Number of Ports  Trunks  Analog Trunks (COT):* 4,000  T1/PRI Channels:* 4,000  SIP Trunks:* 4,000  Stations  Digital Terminals:* 4,000  Analog Terminals:* 4,000  IP Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Processors	Intel Dual Core Duo 2.16GHz
Trunks  Analog Trunks (COT):* 4,000  T1/PRI Channels:* 4,000  SIP Trunks:* 4,000  Stations  Digital Terminals:* 4,000  Analog Terminals:* 4,000  IP Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Gateway Chassis Slots	17
Analog Trunks (COT):* 4,000 T1/PRI Channels:* 4,000 SIP Trunks:* 4,000 Stations Digital Terminals:* 4,000 Analog Terminals:* 4,000 IP Terminals (hard/soft): 4,000 Networking FCCS networking (IP): 64 nodes CCIS networking (T1/IP): 64 nodes Ports: up to 192,000 Standards Devices: SIP-enabled Databases: LDAP-compliant Languages: Java and XML Wireless LAN: 802.11 a/b/g Other: 802.3af Applications Internal ACD: Max 1000 stations OAI support: UNIVERGE 3rd party apps Conference Bridge: Max 32 ports/card; Max 255 cards	Number of Ports	6,144
T1/PRI Channels:* 4,000  Stations  Digital Terminals:* 4,000  Analog Terminals:* 4,000  Pr Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Trunks	
SIP Trunks:* 4,000  Stations  Digital Terminals:* 4,000  Analog Terminals:* 4,000  IP Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Analog Trunks (COT):*	4,000
Stations  Digital Terminals:* 4,000  Analog Terminals:* 4,000  IP Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	T1/PRI Channels:*	4,000
Digital Terminals:* 4,000  Analog Terminals:* 4,000  IP Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	SIP Trunks:*	4,000
Analog Terminals:* 4,000  IP Terminals (hard/soft): 4,000  Networking  FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Stations	
IP Terminals (hard/soft): 4,000	Digital Terminals:*	4,000
Networking FCCS networking (IP): 64 nodes CCIS networking (T1/IP): 64 nodes Ports: up to 192,000 Standards Devices: SIP-enabled Databases: LDAP-compliant Languages: Java and XML Wireless LAN: 802.11 a/b/g Other: 802.3af  Applications Internal ACD: Max 1000 stations OAI support: UNIVERGE 3rd party apps Conference Bridge: Max 32 ports/card; Max 255 cards	Analog Terminals:*	4,000
FCCS networking (IP): 64 nodes  CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	IP Terminals (hard/soft):	4,000
CCIS networking (T1/IP): 64 nodes  Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Networking	
Ports: up to 192,000  Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	FCCS networking (IP):	64 nodes
Standards  Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAl support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	CCIS networking (T1/IP):	64 nodes
Devices: SIP-enabled  Databases: LDAP-compliant  Languages: Java and XML  Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAl support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Ports:	up to 192,000
Databases:  LDAP-compliant  Languages:  Java and XML  Wireless LAN:  802.11 a/b/g  Other:  802.3af  Applications  Internal ACD:  Max 1000 stations  OAI support:  UNIVERGE 3rd party apps  Conference Bridge:  Max 32 ports/card; Max 255 cards	Standards	
Languages:  Java and XML  Wireless LAN:  802.11 a/b/g  Other:  802.3af  Applications  Internal ACD:  Max 1000 stations  OAl support:  UNIVERGE 3rd party apps  Conference Bridge:  Max 32 ports/card; Max 255 cards	Devices:	SIP-enabled
Wireless LAN: 802.11 a/b/g  Other: 802.3af  Applications  Internal ACD: Max 1000 stations  OAl support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Databases:	LDAP-compliant
Other: 802.3af  Applications Internal ACD: Max 1000 stations OAI support: UNIVERGE 3rd party apps Conference Bridge: Max 32 ports/card; Max 255 cards	Languages:	Java and XML
Applications Internal ACD: Max 1000 stations OAI support: UNIVERGE 3rd party apps Conference Bridge: Max 32 ports/card; Max 255 cards	Wireless LAN:	802.11 a/b/g
Internal ACD: Max 1000 stations  OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Other:	802.3af
OAI support: UNIVERGE 3rd party apps  Conference Bridge: Max 32 ports/card; Max 255 cards	Applications	
Conference Bridge: Max 32 ports/card; Max 255 cards	Internal ACD:	Max 1000 stations
	OAI support:	UNIVERGE 3rd party apps
	Conference Bridge:	Max 32 ports/card; Max 255 cards

Regulatory Compliance	FCC part 15, Class A & part 68
	• UL 1459
	Section 508 compliant
	CSA standard C 22.2 No. 225
	CE Mark
	Industry Canada (IC) CS-03

<sup>\*</sup> Based upon system configuration

The SV8500's architecture accommodates and supports our customer's pre-existing system equipment and terminals while offering an extensive IP feature set in a flexible, scalable secure package.

Whether a business is an existing customer or one that is new to NEC, they can always be confident in the knowledge that they have the latest communications technology and applications. Because this solution is one of NEC's global offerings, development for UNIVERGE SV8500 Communications Servers will continue for years to come.

#### **Available Options**

Optional 1 RU MPC Chassis Cards: 2 Slots Per MPC		
6COT MG	6 analog trunks	
4LC2COT	4 analog & 2 trunks	
PRI MG	1 PRI trunk	
8LC	8 analog stations	
VS-32 Conf. Module	32 conference ports	
T1 MG	1 T1 trunk	
MGSIP (16)	16 SIP trunks	
SR-MGC (S)	Supports up to 200 Ports	
Optional 1.5 RU Media Gateways		
SR-MGC (E)	Stand-alone, supports up to 1000 ports	
MG-SIP (128)	Stand-alone, supports up to 128 SIP Trunks	

Optional Features	2 redundant Ethernet ports     High Speed internal communication bus     Redundant power supply options     Redundant processors     Encryption     UCE Mobility     UNIVERGE IP & Digital Terminals (Desktop & DECT)     Dual input/output cards

Optional Gateway Chassis	
Height:	8 RU high
Availability:	For high-density TDM digital and analog interface cards
Universal Card Slots:	17

Optional IP Gateway	
IP Gateway (IPG)	32 Digital Series E, i or DT300 terminals
	32 Standard Analog Telephones

Empowered by Innovation



Corporate Headquarters (Japan) NEC Corporation

nec.com

North America (USA & Canada) NEC Corporation of America

necam.com

APAC
NEC Asia Pacific Pte Ltd

NEC Enterprise Solutions
NEC Europe Ltd

About NEC Corporation of America Headquartered in Irving, Texas, NEC Corporation of America is a leading provider of innovative IT, network and communications products and solutions for service carriers, Fortune 1000 and SMB businesses across multiple vertical industries, including Healthcare, Government, Education and Hospitality, NEC Corporation of America delivers one of the industry's broadest portfolios of technology solutions and professional services, including unified communications, wireless, voice and data, managed services, server and storage infrastructure, optical network systems, microwave radio communications and biometric security. NEC Corporation of America is a wholly-owned subsidiary of NEC Corporation, a global technology leader with operations in 30 countries and more than \$38.5 billion in revenues. For more information, please visit necam.com.