

Powerful entry-level business media phones for today's cubicle workers handling a low to moderate volume of calls delivering crystal clear communications



The Polycom® VVX® 300 is an expandable business media phone that delivers crystal clear communications, enhanced collaboration and personal productivity.

### **Simplicity and ease-of-use**

The VVX 300 phone brings high-quality, cost effective solutions to any environment through advanced UC features. The intuitive user interface of the VVX 300 makes usability and navigation easy and requires minimal training.

### **Customizable and expandable**

The VVX 300 phone provides personalized information at a glance, through built-in web applications and custom backgrounds. The VVX 300 phone also comes ready for future expansion modules as your users' needs and business grows.

### **Unsurpassed voice quality and clarity**

The VVX 300 delivers breakthrough Polycom® HD Voice™ quality for life-like conversations while minimizing fatigue making calls more efficient and productive.

### **Market-leading open standards interoperability**

Designed for enhanced interoperability, the VVX 300 leverages and complements the other existing IT investments in your business. With the broadest call server interoperability in the industry, the Polycom VVX 300 entry level business media phone can become the flexible and future-proof foundation for any organization's unified communications strategy.

### **Maximize productivity**

Give your front line workers the best experience with this high quality two-line business media phone.

### **Benefits**

- Improve productivity for cubicle workers and call center operators through an intuitive easy to use user interface
- Make more efficient and productive calls with the unparalleled voice clarity of Polycom® HD Voice™
- Leverage previous IT infrastructure investments—deploy VVX 300 business media phones on your existing network without needing to upgrade your call control platform

# Polycom® VVX® 300 Series

## USER INTERFACE FEATURES

- Backlit 8-level Grayscale graphical LCD (208 x 104) resolution
- Voicemail support
- Adjustable base height
- Unicode UTF-8 character support. Multilingual user interface including Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

## AUDIO FEATURES

- Polycom HD Voice technology delivers life-like voice quality for each audio pathhandset, the hands-free speakerphone, and the optional headset
- Polycom® Acoustic Clarity™ technology providing full-duplex conversations, acoustic echo cancellation and background noise suppression -- Type 1 compliant (IEEE 1329 full duplex)
- Frequency response – 150 Hz – 7 kHz for handset, optional headset and handsfree speakerphone modes
- Individual volume settings with visual feedback for each audio path
- DTMF tone generation (RFC 2833 and in-band)

## HEADSET AND HEARING AID COMPATIBILITY

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment

## CALL HANDLING FEATURES

- 2 lines (programmable line keys)
- Busy Lamp Field (BLF)
- Call timer and call waiting
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way audio conferencing
- One-touch speed dial, redial
- Do not disturb function

## POWER

- External Universal AC Adapter 48VDC; 12W

## APPROVALS

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- Korea KC<sup>3</sup>
- UAE TRA
- Russia GOST-R<sup>3</sup>
- Brazil ANATEL<sup>3</sup>
- Australia A & C Tick

## SAFETY

- UL 60950-1
- CE Mark
- CAN/CSA C22.2 No 60950-1
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- ICASA (add)
- CITC (add)

## OPERATING CONDITIONS

- Temperature: 0 – 40°C (32 – 104°F)
- Relative Humidity: 5% to 95%, noncondensing

## STORAGE TEMPERATURE

- -40 – +70°C (-40 – +160°F)

## POLYCOM VVX 300 COMES WITH:

- VVX 300 console
- Handset with handset cord
- Network (LAN) Cable - CAT-5E

## SIZE

- 19 x 15 x 18 cm (7.5 x 6 x 7 in) (W x H x D)

## PART NUMBERS

- 2200-46135-025 – VVX 400 WW PoE
- 2200-46161-025 – VVX 410 WW PoE

## WEIGHT

- 2.0 lbs (0.9 kg)

## UNIT BOX DIMENSIONS

- 12 x 8.25 x 4.25 in
- 3.1 lbs (1.4 kg)

## COUNTRY OF ORIGIN

- China

## WARRANTY

- One (1) year